Technical Data Sheet (TDS)

OLI NATURA HS Professional Oil

High solid oil for the base treatment of heavily used interior timber surfaces including floorboards, parquet, wood, cork flooring, and furniture. Designed for professional use to achieve maximum protection with a single application.

Features:

- High solid content (~98%) for deep penetration

- Suitable for most timber species

- Machine or manual application

- Extremely high coverage

- Slip-resistant surface

- Highly durable and wear-resistant

- Antistatic and easy to clean

- Resistant to water and household chemicals

- Can be spot repaired

- Natural, breathable finish

Application Areas:

Suitable for untreated timber floors, parquet, cork, OSB flooring, veneers, furniture, and joinery.

Compliance:

- EU Decopaint Directive compliant

- DIN 53160 (saliva and sweat resistant)

- DIN EN 71-3 (toy safety)

- DIBt emissions tested

- Free from formaldehyde and aromatic solvents

- No biocides or preservatives

Composition:

Modified vegetable oils including linseed oil; lead-free drying agents.

Application:

1. Stir thoroughly.

2. Apply 20–40 g/m² evenly using brush, roller, or applicator.

3. After 20–30 minutes, work into surface with green pad.

4. Final polish after 4–6 hours using cloth or white pad.

5. Full cure achieved in 2–3 days. Protect from water during this time.

Surface Preparation:

Surface must be dry, clean, and free from grease. Sand timber to P100–150. Test on tropical timbers before use.

Maintenance:

Use OLI Natura Maintenance Oil for refreshing. For cleaning, use OLI Natura Wood Soap.

Storage:

Store in original sealed container for up to 24 months. Do not exceed 30°C.

Safety:

Risk of spontaneous combustion. Dispose of oil-soaked cloths safely. Refer to SDS for full safety guidance.

Distributed by Superior Timber Coatings

Unit 2/13 Thames Avenue, Klemzig SA 5087

Phone: 1300 887 853

Email: sales@stcoatings.com.au