



720 Easystain

Fade Resistant Dye Stain

DESCRIPTION:	720 Easystain is a non-grain raising interior dye stain that highlights the natural grain of solid and veneer timbers. It minimizes masking of the grain's features which gives a beautiful and appealing look.
FEATURES & BENEFITS:	✓ Easy stain to apply by spray, dip, or cloth pad ✓ Minimize flecking and blotching on the timber substrate ✓ Reduces shadowing in corners caused by wet overlaps ✓ Stain provides excellent clarity ✓ Toning – up to 10% of stain can be added to any of the Superior Timber Coatings solvent-based clear products for toning ✓ To provide natural timber colours on doors, wall panels, kitchen cabinets, shop fitting, furniture, and most interior timber substrates.
COLOURS:	Available in a range of traditional and modern colours. Special colours may be made upon request. (A once off tinting fee applies)
TYPICAL APPLICATIONS:	A number of excellent Superior Timber Coatings clear systems can be used over the 720 Easystain. (Speak to your Technical Sales Consultant for a system that best meets your requirements)
DRYING TIMES:	➤ <u>Touch-dry:</u> Approx. 10-15 minutes ➤ <u>Sealer coat:</u> Approx. 30-40 minutes ✓ Tested at 25°C and 60% relative humidity.
THINNING:	720 Easystain is supplied ready for use. However, to achieve lighter tones reduce with TZ720 Stain Thinner, TZ35 PU Fast Thinner or TZ14S Reducer.
THEORETICAL SPREAD RATE:	16 sq/m per litre (cloth pad), 9 sq/m per litre (spray)
CLEAN UP:	Clean all equipment immediately after use with TZ720 Stain Thinner, TZ35 PU Fast Thinner or TZ075 Lacquer Thinner.
SHELF LIFE:	12 months minimum in sealed containers.
CONTAINER SIZE:	1lt, 2lt, 4lt, 10lt, 20lt. (or any amount can be made to meet the customer's requirements.)



720 Easystain - Fade Resistant Dye Stain

APPLICATION METHODS:

Suction & Gravity Gun: Use 1.5mm /1.7mm orifice with 280kpa (35psi). Use a medium to wide fan when applying 720 Easystain.

Pressure Pot: Use 1.3mm /1.5mm orifice with 280kpa (35psi). Use a medium to wide fan when applying 720 Easystain.

Air Assisted, Air Mix & Airless Guns: Not Recommended.

NOT RECOMMENDED: 720 Easystain is not recommended for exterior use.

PRECAUTIONS: 720 Easystain contains flammable solvents. Keep away from heat and open flame. Apply in area with effective exhaust system and comply with local regulations applicable to spray painting. Air fed respiratory protective equipment and gloves should be worn when this product is used. Area should be isolated from other people during application.

Do not use product under 10°C or over 80% humidity.

After staining with rags, they **MUST** be submerged in water to prevent combustion within the rag.

Refer to the SDS before using.

Flash Points:	Packaging Group:	UN No:	Haz Chem Code:	Precaution:
Over 23°C	III	1263	3[Y]	Flammable

Technical information given verbally or in writing is based on knowledge and research, given in good faith, and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether expressed or implied for any defect in quality, or for lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from date of delivery. It is recommended that the user do a test to determine the suitability of the product meets their requirements. Freedom from patent restrictions is not implied.