

SAFETY DATA SHEET

OLI-NATURA HS Härter

Distributed in Australia by Superior Timber Coatings

SECTION 1: Identification of the Substance and Supplier

Product Name: OLI-NATURA HS Härter

Product Code: A03662

Recommended Use: Curing agent for OLI-NATURA HS Profi Oil and HS Hardwax Oil

Australian Supplier:

Superior Timber Coatings

Phone: 1300 887 853

Eastern States: sales@stcoatings.com.au

SA / WA / NT: salessa@stcoatings.com.au

Emergency: Poisons Information Centre (Australia) – 13 11 26

SECTION 2: Hazard Identification

Classification (CLP): Acute Tox. 4 (Inhalation), Skin Sens. 1, STOT SE 3

H332 Harmful if inhaled

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

EUH204 Contains isocyanates. May produce an allergic reaction

Signal Word: Warning

SECTION 3: Composition / Information on Ingredients

Hexamethylene-1,6-diisocyanate homopolymer (CAS 28182-81-2): 95–100%

Hexamethylene di-isocyanate (CAS 822-06-0): <1%

SECTION 4: First Aid Measures

Inhalation: Move to fresh air immediately.

Skin: Wash with soap and water. Do not use solvents.

Eyes: Rinse with water for 10–15 minutes and seek medical advice.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

SECTION 5: Fire-Fighting Measures

Suitable extinguishing media: Alcohol-resistant foam, CO₂, dry powder, water mist.

Unsuitable: High-pressure water jet.

Decomposition may release hazardous vapours.

SECTION 6: Accidental Release Measures

Ensure ventilation. Prevent entry into drains or waterways.

Absorb with inert material and dispose appropriately.

SECTION 7: Handling and Storage

Avoid inhalation and skin contact.

Store tightly closed in a cool, ventilated area.

SECTION 8: Exposure Controls / Personal Protection

Respiratory protection required during spraying.
Nitrile gloves, safety glasses, protective clothing required.

SECTION 9: Physical and Chemical Properties

Physical state: Liquid
Flash point: >100 °C
Density: 1.1 g/cm³
Solid content: 100%

SECTION 10: Stability and Reactivity

Stable under normal conditions.
Reacts slowly with water producing CO₂.

SECTION 11: Toxicological Information

Harmful if inhaled. May cause allergic skin and respiratory reactions.

SECTION 12: Ecological Information

Do not allow product to enter drains or waterways.

SECTION 13: Disposal Considerations

Dispose as hazardous waste according to local regulations.
Waste code: 08 01 11

SECTION 14: Transport Information

Not classified as dangerous goods.

SECTION 15: Regulatory Information

VOC content: 0 g/L
Water hazard class: 1

SECTION 16: Other Information

Prepared for Australian distribution by Superior Timber Coatings.
We scour the globe for the best timber coatings, test them, and bring them to you so you can **Coat With Confidence**.