

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

- Product code TA48
- Trade name: **CLEAR PU SEALER HIGH COVERAGE**

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Paint and relative material only for wood

- Application of the substance / the mixture For professional use

### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

- Further information obtainable from:  
Environmental Health and safety office  
hseoffice@ivmchemicals.com

### 1.4 Emergency telephone number:

From 8.30 to 17.30 0039 038 425 441

Out of the above mentioned hours, Saturdays and Sundays and during periods of closure for holidays please call: 0039 0384 254491

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger

- Hazard-determining components of labelling:  
xylene

**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 1)

- ethyl acetate
- **Hazard statements**
    - H225 Highly flammable liquid and vapour.
    - H315 Causes skin irritation.
    - H319 Causes serious eye irritation.
    - H335 May cause respiratory irritation.
    - H373 May cause damage to the hearing organs through prolonged or repeated exposure.
  - **Precautionary statements**
    - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
    - P241 Use explosion-proof electrical/ventilating/lighting/equipment.
    - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
    - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
    - P405 Store locked up.
    - P501 Dispose of contents/container in accordance with local.
  - **2.3 Other hazards**
    - **Results of PBT and vPvB assessment**
      - **PBT:** Not applicable.
      - **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
  - **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene ⚠ Flam. Liq. 3, H226 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	30-49.9%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119488216-32-XXXX	ethylbenzene ⚠ Flam. Liq. 2, H225 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	5-9.99%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-4.99%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-4.99%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
  - **General information:**
    - Immediately remove any clothing soiled by the product.
    - Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

**Product code TA48****Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 2)

- **After inhalation:**  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Remove contaminated clothing.  
Immediately wash with water and soap, or a recognized skin cleanser, and rinse thoroughly.  
Take off immediately all contaminated clothing, include underwear and shoes (if necessary).  
Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. I medical advise is needed have products container or label at hand.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
For symptoms and effects caused by substances, see chap. 11th
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
  - *Suitable extinguishing agents:* Alcohol resistant foam, CO, powder, water spray/mist.
  - *For safety reasons unsuitable extinguishing agents:*  
Do not use a jet water stream as it may scatter and spread fire.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**  
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
  - **Protective equipment:**  
Hardhat with visor, fireproof clothing, suitable gloves and if necessary mouth respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

**Product code TA48****Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 3)

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if indicated, is from delivery date.

In cases there is no reported deadline, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **7.3 Specific end use(s)**

Those typical of the product and the instructions in the data sheet if required.

**SECTION 8: Exposure controls/personal protection**
· **Additional information about design of technical facilities:** No further data; see item 7.· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****100-41-4 ethylbenzene**

WEL	Short-term value: 552 mg/m , 125 ppm
	Long-term value: 441 mg/m , 100 ppm
	Sk

**110-19-0 isobutyl acetate**

WEL	Short-term value: 903 mg/m , 187 ppm
	Long-term value: 724 mg/m , 150 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL	Short-term value: 548 mg/m , 100 ppm
	Long-term value: 274 mg/m , 50 ppm
	Sk

**141-78-6 ethyl acetate**

WEL	Short-term value: 400 ppm
	Long-term value: 200 ppm

· **DNELs****1330-20-7 xylene**

Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	289 mg/mc (Workers)
	DNEL	77 mg/mc (Workers)
Irritation of skin	DNEL	180 mg/kg bw/d (Workers)

(Contd. on page 5)

**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 4)

<b>100-41-4 ethylbenzene</b>		
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	293 mg/mc (Workers)
	DNEL	77 mg/mc (Workers)
Irritation of skin	DNEL	180 mg/kg bw/d (Workers)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Inhalative	DNEL	275 mg/mc (Workers)
Irritation of skin	DNEL	153.5 mg/kg bw/d (Workers)
<b>141-78-6 ethyl acetate</b>		
Oral	DNEL	4.5 mg/kg bw/d (popolazione)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	1468 mg/mc (Workers)
	DNEL	734 mg/mc (popolazione)
	DNEL	734 mg/mc (Workers)
	DNEL	367 mg/mc (popolazione)
Irritation of skin	DNEL	63 mg/kg bw/d (Workers)
		37 mg/kg bw/d (popolazione)

## · PNECs

<b>1330-20-7 xylene</b>	
PNEC Acqua dolce/water/woda sjdka/eau/agua	0.327 mg/L ( )
PNEC Suolo/earth/suelo/sol/gleba/	2.31 mg/kg ( )
<b>100-41-4 ethylbenzene</b>	
PNEC Acqua dolce/water/woda sjdka/eau/agua	0.1 mg/L ( )
PNEC Suolo/earth/suelo/sol/gleba/	2.68 mg/kg ( )
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
PNEC Acqua dolce/water/woda sjdka/eau/agua	0.635 mg/L ( )
PNEC Suolo/earth/suelo/sol/gleba/	0.29 mg/kg ( )
<b>141-78-6 ethyl acetate</b>	
PNEC Acqua dolce/water/woda sjdka/eau/agua	0.26 mg/L ( )
PNEC Suolo/earth/suelo/sol/gleba/	0.24 mg/kg ( )

## · Ingredients with biological limit values:

<b>1330-20-7 xylene</b>	
BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles (EN166)

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Strong

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C

· **Flash point:**

-4 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

315 °C

· **Decomposition temperature:**

Not determined.

· **Self-igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.0 Vol %

· **Upper:**

11.5 Vol %

(Contd. on page 7)



**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 6)

· Vapour pressure at 20 °C:	97 hPa
· Density at 20 °C:	0.992 g/cm
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C:	25 s (ISO 6 mm)
· Oxidising properties :	N.A.
· Solvent content:	
· VOC and Total VOC (organic solvents + reactive solvents if any)	51.73 %
· VOC (EC)	513.2 g/l
· Solids content:	48.3 %
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** Typical of the product as indicated in the data sheet
- **10.2 Chemical stability**  
 The product is stable in normal conditions of storage and use recommended  
 · **Thermal decomposition / conditions to be avoided:**  
 No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**  
 Reacts with oxidising agents.  
 Vapours may form explosive mixtures with air
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
 In case of possible formation of combustion:  
 Carbon monoxide and carbon dioxide

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**  
 · **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
<b>1330-20-7 xylene</b>		
Oral	LD50	3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	15486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

(Contd. on page 8)

**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 7)

Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20001 mg/kg (Con)
Inhalative	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
	LC0	22.6 ppm (mouse)

- **Primary irritant effect:**
  - **Skin corrosion/irritation**  
Causes skin irritation.
  - **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
  - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
  - **Carcinogenicity** Based on available data, the classification criteria are not met.
  - **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

· <b>Aquatic toxicity:</b>	
<b>100-41-4 ethylbenzene</b>	
EC50	75 mg/l (daphnia) (48 h)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC50	1001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
<b>141-78-6 ethyl acetate</b>	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
  - **Additional ecological information:**
    - **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.

(Contd. on page 9)



**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**


(Contd. of page 8)

- *vPvB: Not applicable.*
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
  - **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Hand over to hazardous waste disposers.  
The code number of the product as is 080111
  - **Uncleaned packaging:**
    - **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |                                      |
|---|--------------------------------------|
| · <b>14.1 UN-Number</b>   |                                      |
| · <b>ADR, IMDG, IATA</b>  | UN1263                               |
| · <b>14.2 UN proper shipping name</b>   |                                      |
| · <b>ADR</b>  | UN1263 PAINT, special provision 640D |
| · <b>IMDG</b>   | PAINT                                |
| · <b>IATA</b>   | Paint                                |
| · <b>14.3 Transport hazard class(es)</b>  |                                      |
| · <b>ADR, IMDG, IATA</b>  |                                      |
|  |                                      |
| · <b>Class</b>  | 3 Flammable liquids.                 |
| · <b>Label</b>  | 3                                    |
| · <b>14.4 Packing group</b>   |                                      |
| · <b>ADR, IMDG, IATA</b>  | II                                   |
| · <b>14.5 Environmental hazards:</b>  |                                      |
| · <b>Marine pollutant:</b>  | No                                   |
| · <b>14.6 Special precautions for user</b>  | Warning: Flammable liquids.          |
| · <b>Danger code (Kemler):</b>  | 33                                   |
| · <b>EMS Number:</b>  | F-E, S-E                             |
| · <b>Stowage Category</b>   | B                                    |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>    | Not applicable.                      |
| · <b>Transport/Additional information:</b>  |                                      |
| · <b>ADR</b>  |                                      |
| · <b>Limited quantities (LQ)</b>  | 5L                                   |

(Contd. on page 10)

**Product code TA48**  
**Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 9)

· <i>Excepted quantities (EQ)</i>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <i>Transport category</i>	2
· <i>Tunnel restriction code</i>	D/E
<hr/>	
· <b>IMDG</b>	
· <i>Limited quantities (LQ)</i>	5L
· <i>Excepted quantities (EQ)</i>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 96/82/EC

Flammable

Limit 1: 5000 t

Limit 2: 50000 t

Directive n. : 80/1107/CEE, n. 82/605/CEE, n. 83/477/CEE, n. 86/188/CEE e n. 88/642/CEE, 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2002/44,2003/10/CE, 2003/18/CE , 2004/40/CE,2006/25

· *Various regulations* For uses not regulated by Directive 2004/42/EC-For professional use only

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Department issuing MSDS:** IVM Chemicals Srl

(Contd. on page 11)

**Product code TA48****Trade name: CLEAR PU SEALER HIGH COVERAGE**

(Contd. of page 10)

- **Contact:** Carlo Porta

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

- **Sources**

Directive 1999/45/EC and following amendments  
 Directive 67/548/EEC and following amendments and adjustments  
 Agency ECHA web site  
 INRS Fiche Toxicologique

- **\* Data compared to the previous version altered.**