

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Rt qf weveqfg TO9751
- Vtcfg pco g<**DIAMANTE POLYURETHANE CLEAR TOP COAT 65GL**
- 3040Tgqxcpxvlf gpvllgf wugu qhv j g wuducpeg qt o kwtg cpf wugcf xhgf ci chpw
Painting product for coating and / or decoration of manufactured articles.
- Crrnecvqpp qhv j g wuducpeg Ij g o kwtg For professional use

1.3 Details of the supplier of the safety data sheet

·Manufacturer/Supplier:

IVM Chemicals srl Viale della Stazione 3 -27020 Parona (PV) Italy tel +39 038425441

1.3.2 Importer

Name: AKZOLUX AUSTRALIA T/as: SUPERIOR TIMBER COATINGS

Address: 13/257 COLCHESTER ROAD KILSYTH, VICTORIA, AUSTRALIA Email:tom@stcoatings.com.au

·Information department:

Environmental Health and safety office hseoffice@ivmchemicals.com

·Emergency telephone number:

From 8.30am to 3.30pm (AEST) +61 03 9761 6899 Out of the above mentioned hours, Saturdays and Sundays and during periods of closure for holidays please call: +61410 635 016

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- EncuHecvqpp ceeqtf lpi vj Tgi wrcvqpp *GE+Pq 3494H22:



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

- Ncdgnlpi ceeqtf lpi vj Tgi wrcvqpp *GE+Pq 3494H22:
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 1)

· *J c/ctf r l e w q i t c o u*



GHS02 GHS05 GHS07 GHS08

· *U i p c n y q t f* Danger

· *J c/ctf/f g y g t o k p l p i e q o r q p g p w u q h r d g n l p i <*
xylene
butan-1-ol
toluene
ethyl acetate

· *J c/ctf u e v g o g p w u*

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H361d Suspected of damaging the unborn child.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

· *R t g e c w l k p c t { u e v g o g p w u*

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local.

· **2.3 Other hazards**

· *T g w n u q h R D V c p f x R x D c u g u o g p v*
· RDV < Not applicable.
· xRxD < Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· *F g u e t l r v a p <* Mixture: consisting of the following components.

(Contd. on page 3)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented






















Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 2)

<i>· Fcpi gtqweqo rpgpwnk</i>		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene  Flam. Liq. 3, H226  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	20-24.99%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	15-19.99%
CAS: 110-19-0 EINECS: 203-745-1 Reg.nr.: 01-2119488971-22-XXXX	isobutyl acetate  Flam. Liq. 2, H225  STOT SE 3, H336	10-12.49%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226  STOT SE 3, H336	5-9.99%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119488216-32-XXXX	ethylbenzene  Flam. Liq. 2, H225  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332	2.5-4.99%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-XXXX	toluene  Flam. Liq. 2, H225  Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	≥3-<4.99%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-XXXX	butan-1-ol  Flam. Liq. 3, H226  Eye Dam. 1, H318  Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.49%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23-XXXX	2-methylpropan-1-ol  Flam. Liq. 3, H226  Eye Dam. 1, H318  Skin Irrit. 2, H315; STOT SE 3, H335-H336	1%

· Cff lqpcnlpqto ctkp <For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· I gpgtcnlpqto ctkp <

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· Chgt lqj ctkp <

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751**Trade name: DIAMANTE CLEAR TOP-COAT 65GL**

(Contd. of page 3)

- *Chgt unip eqpw ev*
Remove contaminated clothing.
Immediately wash with water and soap, or a recognized skin cleanser, and rinse thoroughly.
Take off immediately all contaminated clothing, include underwear and shoes (if necessary).
Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. I medical advise is needed have products container or label at hand.
- *Chgt gfg eqpw ev*
Rinse opened eye for several minutes under running water. Then consult a doctor.
- *Chgt uy cnyy lpi* <Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, see chap. 11th
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - *Uwkdng gz vpi wuj lpi ci gpw* <Alcohol resistant foam, CO, powder, water spray/mist.
 - *Hqt uchv tgc upu wuwkdng gz vpi wuj lpi ci gpw*
Do not use a jet water stream as it may scatter and spread fire.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - *Rt qvewxg gwlr o gpw*
Hardhat with visor, fireproof clothing, suitable gloves and if necessary mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

GB

(Contd. on page 5)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 4)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- *Ķpĥto cĥqĥ cdqwwĥĥg / cpf gznqĥqĥ rtqĥĥqĥ* < Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

- *Uqĥci g<*
 - *Tgs wĥgo gĥuĥ dg o gvdĥ uqĥgtqgo ucpf tgegrwengĥ* < Store in a cool, well-ventilated area, away from heat and sources of ignition
 - Provide solvent resistant, sealed floor.
 - Observe the label precautions, the expiration date for the use, if indicated, is from delivery date.
 - In cases there is no reported deadline, it means that the product must be used within 8 months.
 - *Ķpĥto cĥqĥ cdqwwĥqĥci g ĥp qĥg eqo o qĥ uqĥci g ĥcĥĥĥ* < Not required.
 - *Hĥĥj gt ĥpĥto cĥqĥ cdqwwĥqĥci g eqpf ĥĥqĥĥ* < Keep container tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s)

Those typical of the product and the instructions in the data sheet if required.

SECTION 8: Exposure controls/personal protection

- *Cffĥĥqĥpcĥpĥto cĥqĥ cdqwwfgĥi p qĥĥej pĥcĥĥcĥĥĥg* < No further data; see item 7.

8.1 Control parameters

· <i>Ķpi tgf ĥpĥuĥ ĥj nĥo ĥxcnĥguĥj cvtgs wĥg o qĥĥqĥĥi cvĥj gĥ qtĥrĥeg<</i>	
141-78-6 ethyl acetate (15-19.99%)	
WEL	Short-term value: 1468 mg/m , 400 ppm Long-term value: 734 mg/m , 200 ppm
100-41-4 ethylbenzene (2.5-4.99%)	
WEL	Short-term value: 552 mg/m , 125 ppm Long-term value: 441 mg/m , 100 ppm Sk
71-36-3 butan-1-ol (1-2.49%)	
WEL	Short-term value: 154 mg/m , 50 ppm Sk
78-83-1 2-methylpropan-1-ol (1%)	
WEL	Short-term value: 231 mg/m , 75 ppm Long-term value: 154 mg/m , 50 ppm

(Contd. on page 6)

GB

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 5)

123-86-4 n-butyl acetate (<0.1%)

WEL Short-term value: 966 mg/m , 200 ppm
Long-term value: 724 mg/m , 150 ppm

· *FP G_{Nu}***1330-20-7 xylene**

Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	289 mg/mc (Workers)
	DNEL	77 mg/mc (Workers)
Irritation of skin	DNEL	180 mg/kg bw/d (Workers)

141-78-6 ethyl acetate

Oral	DNEL	4.5 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	1,468 mg/mc (Workers)
		734 mg/mc (population)
	DNEL	734 mg/mc (Workers)
		367 mg/mc (population)
Irritation of skin	DNEL	63 mg/kg bw/d (Workers)
		37 mg/kg bw/d (population)

110-19-0 isobutyl acetate

Oral	DNEL	5 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	600 mg/mc (Workers)
		300 mg/mc (population)
	DNEL	300 mg/mc (Workers)
		35.7 mg/mc (population)
Irritation of skin	DNEL acuto/agudo/ostre/aigu/acute/akut	5 mg/kg bw/d (population)
	DNEL	10 mg/kg bw/d (Workers)
		5 mg/kg bw/d (population)

108-65-6 2-methoxy-1-methylethyl acetate

Inhalative	DNEL	275 mg/mc (Workers)
Irritation of skin	DNEL	153.5 mg/kg bw/d (Workers)

100-41-4 ethylbenzene

Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	293 mg/mc (Workers)
	DNEL	77 mg/mc (Workers)
Irritation of skin	DNEL	180 mg/kg bw/d (Workers)

108-88-3 toluene

Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	384 mg/mc (Workers)
	DNEL	192 mg/mc (Workers)
Irritation of skin	DNEL	384 mg/kg bw/d (Workers)

78-83-1 2-methylpropan-1-ol

Inhalative	DNEL	310 mg/mc (Workers)
------------	------	---------------------

· *RPGE_u***1330-20-7 xylene**

PNEC Acqua dolce/water/woda słodka/eau/agua/	0.327 mg/L (_)
PNEC Suolo/earth/suelo/ /	2.31 mg/kg (_)

(Contd. on page 7)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 6)

141-78-6 ethyl acetate	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.24 mg/L ()
PNEC Suolo/earth/suelo/ /地面	0.148 mg/kg ()
110-19-0 isobutyl acetate	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.17 mg/L ()
PNEC Suolo/earth/suelo/ /地面	0.0755 mg/kg ()
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.635 mg/L ()
PNEC Suolo/earth/suelo/ /地面	0.29 mg/kg ()
100-41-4 ethylbenzene	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.1 mg/L ()
PNEC Suolo/earth/suelo/ /地面	2.68 mg/kg ()
108-88-3 toluene	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.68 mg/L ()
PNEC Suolo/earth/suelo/ /地面	2.89 mg/kg ()
78-83-1 2-methylpropan-1-ol	
PNEC Acqua dolce/water/woda sýðka/eau/agua/水	0.4 mg/L ()
PNEC Suolo/earth/suelo/ /地面	0.0699 mg/kg ()

· Cfflkqpcnklqt o cvkq < The lists valid during the making were used as basis.

8.2 Exposure controls

· Rgtuqpcnrtqvgevkxg gs wlr o gpv<

· I gpgtcnrtqvgevkxg cpf j {i kpkle o gcwmgk<

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Tgur kcvqt { rtqvgevkq<

Short term filter device:

Filter AX



Suitable respiratory protective device recommended. (EN140)

· Rtqvgevkq qhj cpf u<



Protective gloves

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· O cvgtkcnghi mxgu

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is

(Contd. on page 8)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 7)

a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Rgpwtvkwpp vto g qhi rpxg o cvgtkn

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Gfgrtqvgekwpp<



Glasses (EN166) or other protective equipment

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· I gpgtcnkvltato cvkwpp

· Crrgctcpeg<

· Hqto <

Fluid

· Eqvwt <

According to product specification

· Qf qwt <

Characteristic

· Qf qwt vj tguj qtf <

Not determined.

· rJ /xcmwg<

Not determined.

· Ej cpi g kv eqpfkvkwpp

· Ognkpi rkvvltgg/lpi rkvkv<

Undetermined.

· kvkvkndqkvkpi rkvvcvf dqkvkpi tcpi g<

77 °C

· Hrcuj rkvkv<

-4 °C

· Hrcv o cdkkvf kvkvkf. i cvkv<

Not applicable.

· Kpvkvkwpp vgo rgtcvwtg<

315 °C

· Fgeqo rkvkvkwpp vgo rgtcvwtg<

Not determined.

· Cvkvk/lkpvkvkwpp vgo rgtcvwtg<

Product is not selfigniting.

· Gzrvkvkvkwpp rtqrkvkvkvkwpp

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Gzrvkvkvkwpp kvkv kvkv

· Nqv gt <

1 Vol %

· Wrr gt <

12 Vol %

· Xcrqwt rtgvwtg cv42 °C:

97 hPa

· Density at 20 °C:

0.971 g/cm

· Relative density

Not determined.

· Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C:

25 s (ISO 6 mm)

(Contd. on page 9)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 8)

· Oxidising properties :	N.A.
· Solvent content:	
· VOC and Total VOC (organic solvents + reactive solvents if any)	65.38 %
· VOC (EC)	634.9 g/l
· Solids content:	34.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Typical of the product as indicated in the data sheet
- **10.2 Chemical stability**
 The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
 No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 Reacts with strong acids and oxidising agents.
 Vapours may form explosive mixtures with air
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 In case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 · **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)

(Contd. on page 10)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 9)

Inhalative	LC50/4 h	35.7 mg/l (mouse)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (mouse)
78-83-1 2-methylpropan-1-ol		
Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)

- **Primary irritant effect:**
 - **Skin corrosion/irritation**
Causes skin irritation.
 - **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
1330-20-7 xylene	
EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

(Contd. on page 11)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751**Trade name: DIAMANTE CLEAR TOP-COAT 65GL**

(Contd. of page 10)

110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
100-41-4 ethylbenzene	
EC50	438 mg/l (algae) (72h) 1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h) 3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
78-83-1 2-methylpropan-1-ol	
EC50	1,799 mg/l (algae) (72 h) 1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)

- **12.2 Persistence and degradability**

Data refers to the substance Toluene CAS No. 108-88-3

Readily biodegradable (according to OECD criteria and/or EU RAR)

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

The code number of the product as is 080111

(Contd. on page 12)

GB

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 48


Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 11)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · <i>ADR, IMDG, IATA</i> 	UN1263
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · <i>ADR, IMDG, IATA</i> 	PAINT
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · <i>ADR, IMDG, IATA</i> <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · <i>Class</i> · <i>Label</i> 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · <i>ADR, IMDG, IATA</i> 	II
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · <i>Marine pollutant:</i> 	No
<ul style="list-style-type: none"> · 14.6 Special precautions for user · <i>Danger code (Kemler):</i> · <i>EMS Number:</i> · <i>Stowage Category</i> 	Warning: Flammable liquids. 33 F-E, S-E B
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · <i>Limited quantities (LQ)</i> · <i>Excepted quantities (EQ)</i> · <i>Transport category</i> · <i>Tunnel restriction code</i> 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
<ul style="list-style-type: none"> · IMDG · <i>Limited quantities (LQ)</i> · <i>Excepted quantities (EQ)</i> 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 13)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751
Trade name: DIAMANTE CLEAR TOP-COAT 65GL

(Contd. of page 12)

· UN "Model Regulation": UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive n. : 80/1107/CEE, n. 82/605/CEE, n. 83/477/CEE, n. 86/188/CEE e n. 88/642/CEE, 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2002/44,2003/10/CE, 2003/18/CE , 2004/40/CE,2006/25

DIRECTIVE 2012/18/EU

P5c Flammable

Limit 1: 5000 t

Limit 2: 50000 t

· *Various regulations* For uses not regulated by D. 2004/42/EC-For professional use only

· *Qualifying quantity (tonnes) for the application of lower-tier requirements* 5,000 t

· *Qualifying quantity (tonnes) for the application of upper-tier requirements* 50,000 t

· *REGULATION (EC) No 1907/2006 ANNEX XVII* Conditions of restriction: 3, 48

· *National regulations:*

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** Claudia Zanella

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 14)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 48

Revision: 05.02.2020

Product code TO9751**Trade name: DIAMANTE CLEAR TOP-COAT 65GL**

(Contd. of page 13)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Dam. 1: Serious eye damage/eye irritation . Category 1

Eye Irrit. 2: Serious eye damage/eye irritation . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

• *** Data compared to the previous version altered.**