

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Rt qf weveqfg TX19
- Vtcfg pco g< **POLYURETHANE HARDENER**
- 3040Tgqxcpxvlf gpvllgf wguqhvj g wduwpeg qt o kwvtg cpf wgu cf xkgf ci clpw
Painting product for coating and / or decoration of manufactured articles.

1.3 Details of the supplier of the safety data sheet

·Manufacturer/Supplier:

IVM Chemicals srl Viale della Stazione 3 -27020 Parona (PV) Italy tel +39 038425441

1.3.2 Importer

Name: AKZOLUX AUSTRALIA T/as: SUPERIOR TIMBER COATINGS

Address: 13/257 COLCHESTER ROAD KILSYTH, VICTORIA, AUSTRALIA Email:tom@stcoatings.com.au

·Information department:

Environmental Health and safety office hseoffice@ivmchemicals.com

·Emergency telephone number:

From 8.30am to 3.30pm (AEST) +61 03 9761 6899 Out of the above mentioned hours, Saturdays and Sundays and during periods of closure for holidays please call: +61410 635 016

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- EncuHecvqp ceeqtf lpi vq Tgi wrcvqp *GE+Pq 3494H22:



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

- Ncdgnlpi ceeqtf lpi vq Tgi wrcvqp *GE+Pq 3494H22:

The product is classified and labelled according to the CLP regulation.

- J c|ctf rlvqi tco u



GHS02 GHS07 GHS08

- Uki pcny qtf Danger

- J c|ctf/fvgto lplpi eqo rqpqpwhw dgnlpi <
Aromatic polyisocyanate

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19**Trade name: POLYURETHANE HARDENER**

(Contd. of page 1)

ethyl acetate

toluene

- J c / c t f u e v g o g p w u

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

- R t g e c w l a p c t { u e v g o g p w u

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local.

- C f f k l a p c n l p h t o c v l a p <

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

- 2.3 Other hazards

- T g u w u q h R D V c p f x R x D c u g u o g p v

- R D V < Not applicable.

- x R x D < Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures

- F g u e t h r v l a p < Mixture: consisting of the following components.

- F c p i g t q w u e q o r q p g p w u <

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	30-49.99%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	30-49.99%
CAS: 53317-61-6	Aromatic polyisocyanate ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	15-19.99%

(Contd. on page 3)

GB

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 2)		
CAS: 9017-01-0	Aromatic polyisocyanate ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	10-12.49%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-XXXX	toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	≥3-<4.99%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	1-2.49%

· Cff hktqpcnphqt o cktq <For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· I gpgtcnphqt o cktq <

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· Chgt kj ckwq <

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· Chgt untp eqpwev <

Remove contaminated clothing.

Immediately wash with water and soap, or a recognized skin cleanser, and rinse thoroughly.

· Chgt gfg eqpwev <

Rinse opened eye for several minutes under running water. Then consult a doctor.

· Chgt w cmy lpi <Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, see chap. 11th

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Uwkcdig gz vpi whj lpi ci gpvu <Alcohol resistant foam, CO, powder, water spray/mist.

· Hqt uchv tgcupuwpuwkcdig gz vpi whj lpi ci gpvu <

Do not use a jet water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

5.3 Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)

GB

AUSTRALIAN DISTRIBUTOR - Superior Timber Coatings

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19**Trade name: POLYURETHANE HARDENER**

(Contd. of page 3)

· *Rt qvewxg gs wlr o gpv<*

Hardhat with visor, fireproof clothing, suitable gloves and if necessary mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· *kpqt o cvqp cdqwwltg / cpf gznqutqp rtqvewxg<*

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· *Uqtci g<*

· *Tgs wltgo gpvuvj dg o gvd{ wqtgtqo ucpf tgegrweng<*

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if indicated, is from delivery date.

In cases there is no reported deadline, it means that the product must be used within 8 months.

· *kpqt o cvqp cdqwwuqtci g kp qpg eqo o qp wqtci g lcekw<* <Not required.

· *Hwtj gt kpqt o cvqp cdqwwuqtci g eqpf kwqp<*

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s)

Those typical of the product and the instructions in the data sheet if required.

GB

(Contd. on page 5)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· Cffkwpncplqto cvkq cdqwf gki p qhyvej p lncnk ekwkg < No further data; see item 7.

· 8.1 Control parameters

· Kp i t g f l g p u y k j n o k x c n w g u v j c v t g s w k g o q p k q t l p i c v j g y q t m r w e g <	
141-78-6 ethyl acetate (30-49.99%)	
WEL	Short-term value: 1468 mg/m , 400 ppm Long-term value: 734 mg/m , 200 ppm
123-86-4 n-butyl acetate (30-49.99%)	
WEL	Short-term value: 966 mg/m , 200 ppm Long-term value: 724 mg/m , 150 ppm
26471-62-5 m-tolylidene diisocyanate (<0.1%)	
WEL	Short-term value: 0.07 mg/m Long-term value: 0.02 mg/m Sen; as -NCO

· FPGNu

141-78-6 ethyl acetate		
Oral	DNEL	4.5 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	1,468 mg/mc (Workers) 734 mg/mc (population)
	DNEL	734 mg/mc (Workers) 367 mg/mc (population)
Irritation of skin	DNEL	63 mg/kg bw/d (Workers) 37 mg/kg bw/d (population)
123-86-4 n-butyl acetate		
Oral	DNEL	2 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	600 mg/mc (Workers) 300 mg/mc (population)
	DNEL	300 mg/mc (Workers) 35.7 mg/mc (population)
Irritation of skin	DNEL acuto/agudo/ostre/aigu/acute/akut	11 mg/kg bw/d (Workers) 6 mg/kg bw/d (population)
	DNEL	11 mg/kg bw/d (Workers) 6 mg/kg bw/d (population)
108-88-3 toluene		
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	384 mg/mc (Workers)
	DNEL	192 mg/mc (Workers)
Irritation of skin	DNEL	384 mg/kg bw/d (Workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Inhalative	DNEL	275 mg/mc (Workers)
Irritation of skin	DNEL	153.5 mg/kg bw/d (Workers)

· RPGEu

141-78-6 ethyl acetate	
PNEC Acqua dolce/water/woda sypdka/eau/agua/	0.24 mg/L ()

(Contd. on page 6)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 5)

PNEC Suolo/earth/suelo/ /	0.148 mg/kg ()
123-86-4 n-butyl acetate	
PNEC Acqua dolce/water/woda sjo'dka/eau/agua/水	0.18 mg/L ()
PNEC Suolo/earth/suelo/ /	0.0903 mg/kg ()
108-88-3 toluene	
PNEC Acqua dolce/water/woda sjo'dka/eau/agua/水	0.68 mg/L ()
PNEC Suolo/earth/suelo/ /	2.89 mg/kg ()
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC Acqua dolce/water/woda sjo'dka/eau/agua/水	0.635 mg/L ()
PNEC Suolo/earth/suelo/ /	0.29 mg/kg ()

· Cff hktqpcnkhqt o cvtkp < The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Rgtuqpcnrtqvgevkxg gs wlr o gpv<

· I gpgtcnrtqvgevkxg cpf j {i kgpk o gcwtguk<

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Tgur hkvqt { rtqvgevkp <

Short term filter device:

Filter AX



Suitable respiratory protective device recommended. (EN140)

· Rtqvgevkp qhj cpf uk<



Protective gloves

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· O cvgtknqhi nxgu

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Rpgvkvqpv wo g qhi nxg o cvgtkn

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

GB

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 6)

· G{g r t q v e t q p <



Glasses (EN166) or other protective equipment

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· I g p g t c n k p h q t o c v k q p

· C r r g e t c p e g <

· H q t o <

· E q i q w t <

· Q f q w t <

· Q f q w t v j t g u j q i f <

Fluid

According to product specification

Characteristic

Not determined.

· r J / x c m w g <

Not determined.

· E j c p i g h p e q p f k k q p

· O g n k p i r q k p v l t g g / h p i r q k p <

· K p k e n d q k k p i r q k p v c p f d q k k p i t c p i g <

Undetermined.

77 °C

· H r e u j r q k p <

-4 °C

· H r e o o c d k k k f * u i n k f . i c u <

Not applicable.

· K p k k q p v g o r g t c w t g <

315 °C

· F e g e q o r q u k k q p v g o r g t c w t g <

Not determined.

· C w a q / k i p k k q p v g o r g t c w t g <

Product is not selfigniting.

· G z r i q u k x g r t q r g t v k u k <

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· G z r i q u k q p i h o k u k <

· N q y g t <

· W r r g t <

1.2 Vol %

11.5 Vol %

· X c r q w t r t g u w t g e v 42 °C:

97 hPa

· Density at 20 °C:

0.977 g/cm

· Relative density

Not determined.

· Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C:

29 s (ISO 3 mm)

· Oxidising properties :

N.A.

· Solvent content:

· VOC and Total VOC

(organic solvents + reactive solvents if any) 73.73 %

(Contd. on page 8)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 7)

· VOC (EC)	720.4 g/l
· Solids content:	26.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Typical of the product as indicated in the data sheet
- **10.2 Chemical stability**
 The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
 No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 Reacts with strong acids and oxidising agents.
 Vapours may form explosive mixtures with air
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 In case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
141-78-6 ethyl acetate		
Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
53317-61-6 Aromatic polyisocyanate		
Oral	LD50	5,001 mg/kg (mouse)
9017-01-0 Aromatic polyisocyanate		
Oral	LD50	2,001 mg/kg (mouse) (OECD TG 423) Esami tossicologici su un prodotto compatibile
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (mouse)

(Contd. on page 9)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 8)

Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
 - **Serious eye damage/irritation**
Causes serious eye irritation.
 - **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
 - **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity**
Suspected of damaging the unborn child.
 - **STOT-single exposure**
May cause drowsiness or dizziness.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
 - **Aspiration hazard** Based on available data, the classification criteria are not met.
- **More information**
Monomers / polymers isocyanate
Particular characteristics / effects; Over-exposure there is a danger, as a function of concentration, irritation of the eyes, nose, throat and respiratory tract.
Possible the delayed appearance of disorders and development of a form of hypersensitivity (respiratory disorders, cough, asthma). In the case of persons hypersensitive reactions may occur already at concentrations of isocyanate very low, even below the TLV value. In case of prolonged contact with the skin are possible irritant effects and dehydrating.

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:	
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
123-86-4 n-butyl acetate	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h) 3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER


(Contd. of page 9)

- **Additional ecological information:**
 - **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Hand over to hazardous waste disposers.
 The code number of the product as is 080111
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|-----------------------------|
| 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1263 |
| 14.2 UN proper shipping name | |
| · ADR, IMDG, IATA | PAINT |
| 14.3 Transport hazard class(es) | |
| · ADR, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| 14.4 Packing group | |
| · ADR, IMDG, IATA | II |
| 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |

(Contd. on page 11)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and
supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19
Trade name: POLYURETHANE HARDENER

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E

· IMDG

· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive n. : 80/1107/CEE, n. 82/605/CEE, n. 83/477/CEE, n. 86/188/CEE e n. 88/642/CEE, 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2002/44,2003/10/CE, 2003/18/CE , 2004/40/CE,2006/25

DIRECTIVE 2012/18/EU

P5c Flammable

Limit 1: 5000 t

Limit 2: 50000 t

· Various regulations For uses not regulated by D. 2004/42/EC-For professional use only

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 12)

Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 05.02.2020

Version number 201

Revision: 15.01.2020

Product code TX19**Trade name: POLYURETHANE HARDENER**

(Contd. of page 11)

*H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.**H361d Suspected of damaging the unborn child.**H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.**H412 Harmful to aquatic life with long lasting effects.*

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** Claudia Zanella

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2: Serious eye damage/eye irritation . Category 2

Skin Sens. 1: Skin sensitisation . Category 1

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

- *** Data compared to the previous version altered.**